


We UVCare...

Application Optimized UV for Food & Beverage



PURELINE D PH



UV treatment for food and beverage


Our PureLine D PH systems are aimed specifically at providing UV disinfection for product and process waters used in the food and beverage industry. By using a UV system you will disinfect the water, eliminate harmful micro-organisms, reduce the bio-burden, protect against bio-fouling, lead to fewer CIP/SIP cycles and lower operating costs. Each system comes with a UV monitor to measure the germicidal output of the UV system and make it easy to monitor and log performance.

berson

hanovia


aquionics

PureLine D PH™ - UV systems in a typical Food & Beverage water system



KEY FEATURES	WHAT IT GIVES YOU	BENEFITS FOR YOU
INTELLIGENCE		
UV intensity monitor measuring germicidal wavelengths	Continuous verification of performance with in-built low intensity alarm	Easy to monitor and log system performance
OPTIMIZATION		
UV water disinfection	Protect your process waters from microbiological contamination including chlorine resistant <i>Cryptosporidium</i> and <i>Giardia</i>	Does not affect taste and colour of final product
Designed for the food and beverage industry	FDA-approved materials used for all wetted parts	No chemicals
	*Chamber with tri-clamp connections and < 0.38 µm internal finish	Industry compliant materials
	*Automatic wiper (quartz cleaning)	Sanitary design
		Self cleaning
INTEGRATION		
Compact design	Can be fitted to skids	Easy integration

* Option



Model Number	Maximum Power (kW)	Min T ₁₀ (%)	Dimensions (inches)									Approx weight (lbs)	
			A	B	C	D	DN	K*	L	M**	Chamber (Empty)	Control Cabinet	
PureLine D PH 0070	1.6	64	33.5	11.8	10.5	7.2	2.0	13.0	29.5	33.5	99.2	187.4	
PureLine D PH 0080	2.7	91	51.2	28.0	12.6	9.4	3.1	13.0	29.5	33.5	110.2	187.4	
PureLine D PH 0083	2.7	91	51.2	28.0	12.6	9.4	3.9	13.0	29.5	33.5	110.2	187.4	
PureLine D PH 0100	4.4	81	51.2	28.0	12.6	9.4	3.9	13.0	29.5	33.5	110.2	187.4	
PureLine D PH 0209	4.4	90	51.2	26.0	16.5	11.4	5.9	13.0	29.5	33.5	143.3	187.4	
PureLine D PH 0240	5.8	84	51.2	26.0	16.5	11.4	5.9	13.0	35.4	43.3	143.3	187.4	
PureLine D PH 0300	5.8	93	51.2	24.0	19.9	16.1	7.9	13.0	35.4	43.3	308.6	363.8	
PureLine D PH 0350	10.0	70	51.2	26.0	16.5	11.4	5.9	13.0	43.3	63.0	143.3	621.7	
PureLine D PH 0400	16.5	62	51.2	26.0	16.5	11.4	5.9	13.0	43.3	63.0	143.3	621.7	
PureLine D PH 0550	16.5	62	51.2	24.0	19.9	6.1	7.9	13.0	43.3	63.0	308.6	621.7	
PureLine D PH 0900***	25.2	62	51.2	21.7	19.9	6.1	7.9	13.0	35.4	43.3	308.6	363.8	
								13.0	43.3	63.0		621.7	
PureLine D PH 0950***	33000	62	51.2	24.0	19.9	6.1	7.9	13.0	43.3	63.0	308.6	621.7	
								13.0	43.3	63.0		621.7	

* Allow dimension L in front of cabinet for door opening and panel access.

** M dimension includes the space for the cabinet mounting brackets but you need to allow space below the cabinet for cable entry and access (minimum of 9.8").

*** System consists of two cabinets; separate dimensions K, L, M and weights are given for each cabinet.

All dimensions are approximate for clearance purposes only. We have a policy of continuous product development, exact drawings are available on request.

All specifications are subject to change without notification. Your distributor or our account manager can advise on correct sizing and specification requirements.

UV CHAMBER	
Material:	Stainless steel 316L / 1.4404
Internal finish:	As made pipe and tube, welds as laid, electropolished and passivated
External finish:	Sateen polish (120 grit) electropolished and passivated
Process (mating) connections:	Flange EN 1092-1 PN16
Drain connection:	Tri-clamp to ISO 2037
End plate:	Removable end plate
Degree of protection:	IP65 equivalent to NEMA 4 but not for outside use
Arc tube (lamp):	Medium pressure
Arc tube enclosure:	Pure quartz
Number of arc tubes (lamps):	1 (D PH 0070-0300), 4 (D PH 0350-0550), 6 (D PH 0900), 8 (D PH 0950)
Expected lamp life:	8000 hrs, 4000 hrs D PH 0240 and 0300
Temperature sensor:	Yes
UV monitor:	Wet UV monitor (if above minimum T ₁₀)
Working fluid temperature:	41°F to 140°F (176°C unwiped)
Maximum CIP temperature:	203°C with cabinet electrically isolated
Hydrostatically pressure tested:	Yes to PED requirements EN 13445
Chamber mounting:	Horizontal only
Operating pressure:	6 bar
Seals:	EPDM, ADI free, EC 1935/2004, FDA 21 CFR 177.2600 approved

OPTIONS	
Document Support Pack	
Cabinet material: Stainless steel 316	
Operation and Maintenance manual and printed Installation and Commissioning manual in Chinese, English, French, German and Spanish	
Wiper: Automatic (electrically driven) except D 0070	
Flange options: ANSI 150, JIS, Table 'E' and tri-clamp	
Chamber internal finish: <0.38 µm welds polished out, electropolished and passivated	
Lead length: 65.6 ft, 98.4 ft or 164 ft cabinet to chamber	
Maximum CIP temperature: 266°F (panel electrically isolated)	
Welder Document Pack for chamber construction	
Bleed valve: Hygienic valve with tri-clamp connection	
Skid mounting	

OPTIONS (CONTINUED)	
Operating pressure:	10 bar
Power adjustment:	4 level power switching
Vent valve:	Manual valve hygienic design
Cabinet IP rating:	Carbon steel air to air heat exchangers IP 65, NEMA 4 or stainless steel version IP 65, NEMA 4X
Aggressive water package:	For 400 ppm to 20000 ppm chloride water
UVShield™:	Power cut-out for lamp access
Water leak detection:	Detects water leaks from quartz sleeve
Arc tube enclosure:	Doped quartz

CABINET	
Material:	Polyester coated carbon steel
Degree of protection:	IP54 NEMA 12
Supply voltages:	D PH 0070-0083 95 V to 260 V D PH 0100-0300 190 V to 480 V D PH 0350-0950 380 V to 480 V 50/60 Hz, (voltage tolerance ± 10% of nominal)
Operating temperature range:	41°F to 104°F
Relative humidity:	<85% non-condensing
Cooling fans:	Yes
Interconnecting cable:	10 m cabinet to chamber

CUSTOMER OUTPUTS	
4-20 mA passive or active output:	UV intensity %
VFC outputs:	System warning, lamp ready, low UV intensity, common trip, remote reset, ELCB or water leak, system available, local or remote mode

CUSTOMER INPUTS	
4-20 mA passive or active output:	Flow meter
VFC inputs:	Remote stop/start and remote reset

CUSTOMER COMMUNICATIONS PORT	
None	

APPROVALS	
CE marked	



PURELINE D

Also available in our Food & Beverage product range...



PURELINE DC+DCD

Dechlorination and Chlorine
Dioxide removal



PURELINE DO

Ozone removal and
disinfection



PURELINE S

Sugar syrup disinfection



PURELINE S

Sugar syrup disinfection



www.weuvcare.com

BERSON, HANOVIA & AQUIONICS WORKING TOGETHER AS PART OF THE HALMA GROUP.

Netherlands

t: +31 40 2907777
e: sales@bersonuv.com

China

t: +86 21 61679599
e: china@hanovia.com

USA

t: +1 980 256 5700
e: sales@aquionics.com

Germany

t: +49 611 44575375
e: verkauf@hanovia.com

Malaysia

t: +60 16 440 8834
e: asia@hanovia.com

Canada

t: +1 980.256.5700
e: sales@aquionics.com

United Kingdom

t: +44 1753 515300
e: sales@hanovia.com

Mexico

t: +1 980.256.5700
e: sales@aquionics.com



A **Halma** company